



GT/4

- Frontale e Porta 10 mm
- Taglio Laser
- *Front and Door 10 mm*
- *Laser Cut*



Combinazione Elettronica Digitale

- Serratura certificata UNI EN 1300 controllata da un congegno elettronico ad alta affidabilità, dotato di memoria non-volatile.
- Apertura/chiusura con manopola di comando e blocco con elettromagnete.
- Alimentazione interna con batterie alcaline (non incluse).
- Tastiera a membrana con 4 leds dedicati.
- Contatti per batteria esterna ricavati direttamente sulla tastiera.
- Segnalazioni sonore e visive per conferma digitazione, errori e batterie interne in fase di esaurimento.
- Catenacci in acciaio nichelato, girevoli, Ø 22 mm
- Protezione al meccanismo della serratura con piastra in acciaio al manganese.
- Speciali battute della porta per una eccezionale resistenza ai tentativi di effrazione con l'uso di una mazza.
- Robuste saldature interne realizzate con sistema robotizzato.
- Saldatura perimetrale del frontale al corpo realizzata in continuo con sistema robotizzato.
- Ripiano interno.
- Alette di ancoraggio ricavate sui 4 lati del fondo con funzione antistrappo.
- Verniciatura a polvere termoindurente con essiccazione a forno.



Digital Electronic Combination

- Digital electronic lock EN 1300 certified, controlled by a high performing electronic system provided by non-volatile memory.
- Opening/closing with recessed knob and locking by electromagnet.
- Internal power with alkaline battery (not included).
- High quality membrane keyboard with 4 leds.
- Acoustic and visual signals to confirm codes, errors and internal battery deficiency.
- Emergency external power outlet with contacts directly on keyboard.
- Nickel-plated rotating steel bolts ø 22 mm.
- Lock mechanism protected by a manganese-steel plate.
- Special door battens for exceptional resistance against robbery attempts using a sledge hammer.
- Internally welded by a robot-controlled system.
- Front panel seam-welded to the casing by a robot-controlled system.
- Removable internal shelf.
- Anchor tongues on the 4 backs sides against jerks-attempts.
- Oven dried thermo-hardening powder painting.



CERTIFICATA A
NORMA EUROPEA
UNI EN 14450:18-S1
CERTIFIED TO
EUROPEAN STANDARD
EN 14450:18-S1



Art	Misure esterne mm.			Misure interne mm.			Dim. porta mm.		Numero catenacci		Peso	Litri
Code	External dim. mm.			Internal dim. mm.			Door dim. mm.		Number of bolts		Weight	Volume
GT/4	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Oriz/Horiz	Vert	Kg	Lt
	270	390	200	245	365	150	195	300	2	1+1	18	14